

CC ATEX 350

Code	Tipo Type	Modello Model	U	P	Pm (kW)	In (A)	IP/CL	IE3	Mot. (Gr)
1XC3520	CC ATEX	352	M	2	0,55	3,79	55/F	-	80
1XC3511		352	T	2	0,55	1,70	55/F	-	71
1XC3521		354-A	M	4	0,12	1,20	55/F	-	63
1XC3512		354-A	T	4	0,12	0,74	55/F	-	63
A RICHIESTA		354-B	M	4	0,12	1,20	55/F	-	63
1XC3513		354-B	T	4	0,12	0,74	55/F	-	63

Attenzione: non utilizzare le versioni a 2 poli nelle applicazioni a bocca libera o con modeste perdite di carico!
Caution: do not use 2 poles version in free inlet application or with small charge losses!

LIVELLI SONORI | SOUND LEVELS dB(A)

Hz		62,5	125	250	500	1000	2000	4000	8000	TOT
52	Lw	57	68	85	82	83	81	78	73	89
	Lp	36	47	64	61	62	60	57	52	68
354-A	Lw	46	64	66	71	72	70	67	62	76
	Lp	25	43	45	50	51	49	46	41	55
54-B	Lw	37	55	58	62	63	61	58	53	68
	Lp	16	34	37	41	42	40	37	32	47

